

GTWY2000

Mobile Vertical Lifts (Dual Mast)



GTWY8-2000 GTWY10-2000 GTWY12-2000 GTWY14-2000 GTWY16-2000



S.W.L	300kg	300kg	250kg	200kg	150kg
Max. Occupants (Above 10m)	2	2	2	2	1
	/	/	/	1	1
H₁ Working Height	8.00m	10.00m	12.00m	14.00m	16.00m
H₂ Platform Floor Height	6.00m	8.00m	10.00m	12.00m	14.00m
A Overall Length	1.52m	1.52m	1.74m	1.81m	1.81m
B Overall Width	0.81m	0.81m	0.81m	0.81m	0.81m
H₃ Overall Height	1.86m	1.86m	1.86m	2.08m	2.36m
Outrigger Footprint (L/W)	1.82m/1.78m	1.82m/1.78m	2.45m/2.34m	2.45m/2.34m	2.45m/2.34m
Platform Size (Length/Width/C)	1.21mX0.60m	1.21mX0.60m	1.44mX0.60m	1.44mX0.60m	1.44mX0.60m
Ground Clearance	0.07m	0.07m	0.07m	0.07m	0.07m
Wheelbase	1.17m	1.17m	1.41m	1.41m	1.41m
Lifting Motor					
AC	110-230VAC/1.5kw	110-230VAC/1.5kw	110-230VAC/1.5kw	110-230VAC/1.5kw	110-230VAC/1.5kw
DC	12VDC/2.5kw	12VDC/2.5kw	12VDC/2.5kw	12VDC/2.5kw	12VDC/2.5kw
Up/Down Speed	58/40sec	64/44sec	74/44sec	76/47sec	101/59sec
Batteries	2X12V/110Ah	2X12V/110Ah	2X12V/110Ah	2X12V/110Ah	2X12V/110Ah
Integrated Charger	12V/15A	12V/15A	12V/15A	12V/15A	12V/15A
Tyres					
Back Wheels	8in	8in	8in	8in	8in
Front Wheels	7in	7in	7in	7in	7in
Weight	600(AC)/636(DC) kg	624(AC)/662(DC) kg	764(AC)/784(DC) kg	844 (AC)/870(DC) kg	905(AC)/925(DC) kg



Standard Equipment

- Swing Outriggers With Interlock
- Emergency Stop Button
- Battery Charge Indicator
- Electric Limit Switch
- Two Controllers Operation
- Emergency Lowering System
- Leveling Indicator
- Forklift Pockets
- Transport Tie Hole
- All Motion Alarm
- Function With Deadman
- Cylinder Holding Valve

Options

- Overload Sensor
- AC Power To Platform
- DC Power With Charger
- Beacon



Storage Size



Swing Out Outrigger
With Interlock



Ground Control With
Outrigger LEDS

